
































TABLA DE SELECCIÓN DE TERMOSTATOS OSAKA PARA FRÍO

SALIDAS	ALIMENTACIÓN	TAMAÑOS / MEDIDAS					
		32 x 74	38 x 185	Gran Formato (50 x 96 / 97 x 135)	Mural	Rail DIN	
1 RELÉ	230V	F 1*  T 20  F 10* 					
	230...110V	F 100* 					OF 41-AZ 
	12...24V	F 100* 					
2 RELÉS	230...110V	F 200*  OF 51-Z 	COMPACT 2R BLUE INOX  COMPACT 2R 				OF 50-Z 
	12...24V	F 200* 					
3 RELÉS	230...110V	F 300* 	COMPACT 3R BLUE INOX  COMPACT 3R 	TLB 29-N* 	M3 	OF 43-AZ 	
	12...24V	F 300* 					
4 RELÉS	230...110V	OK 33-THR  OK 41  F 500  F 500-RS 	COMPACT 4R BLUE INOX 	TSB 30-BLUE  TSB 55-BLUE  TSB-SPLIT 	SMARTBOX (4/6 Relés) 	OF 43-AZ-4R 	
	12...24V		COMPACT 4R BLUE INOX 				

* Modelos disponibles con opción de display azul: "-BLUE"

** A partir de JUNIO de 2017